

WHAT IS CLAIMED IS:

1. A stapling gun comprising:

a magazine;

a top seat provided with a staple sliding slot and mounted on a top of

said magazine;

a top cover mounted on said top seat; and

a fastening latch pivoted with said top cover;

Wherein, said top seat is provided with at least two retaining portions;

Wherein said top cover is provided with at least two retaining portions, said top cover further provided with a support portion whereby said top cover is mounted on said top seat in such a manner that said retaining portions of said top cover are retained by said retaining portions of said top seat.

Wherein said fastening latch comprises a moving member and a retaining ring, said fastening latch being pivoted with said top cover such that said moving member of said fastening latch is supported by said support portion of said top cover, and that said retaining ring is engaged said retaining portions of said top seat.

2. The stapling gun as defined in claim 1, where in the stapling gun

comprising:

a magazine;

1 a top seat provided with a staple sliding slot and mounted on a top of
2 said magazine;

3 a top cover mounted on said top seat; and

4 a fastening latch pivoted with said top cover;

5 Wherein said top seat is provided with at least two retaining portions
6 and two fastening portions;

7 Wherein said top cover is provided with at least two retaining
8 portions and two fastening portions, said top cover further provided with a
9 support portion whereby said top cover is mounted on said top seat in such a
10 manner that said retaining portions of said top cover are retained by said
11 retaining portions of said top seat, and that said fastening portions of said top
12 cover are engaged with said fastening portions of said top seat.

13 Wherein said fastening latch comprises a moving member and a
14 retaining ring, said fastening latch being pivoted with said top cover such that
15 said moving member of said fastening latch is supported by said support
16 portion of said top cover, and that said retaining ring is engaged said retaining
17 portions of said top seat.

18 3. The stapling guns as defined in claim 1, wherein said retaining
19 portions of said top seat are provided with a retaining slot; wherein said
20 retaining portions of said top cover are provided with a retaining projection
21 whereby said top cover is mounted on said top seat such that said retaining

1 projection of said retaining portions of said top cover is retained in said
2 retaining slot of said retaining portions of said top seat.

3 4. The stapling gun as defined in claim 2, wherein said fastening
4 portions of said top seat are provided with a fastening slot; wherein said
5 fastening portions of said top cover are provided with a retaining projection
6 whereby said top cover is mounted on said top seat such that said retaining
7 projection of said fastening portions of said top cover is retained in said
8 retaining slot of said fastening portions of said top seat.

9 5. The stapling gun as defined in claim 1, wherein said retaining
10 portions of said top seat has a hooked portion which is provided with a holding
11 slot; wherein said fastening latch is pivotally fastened with said top cover such
12 that said retaining ring of said fastening latch is held in said holding slot of said
13 hooked portion of said retaining portions of said top seat.

14